



■ DMX-RDM High Power Contact Relay Module 4x

SYNCROSWITCH

The SyncroSwitch unit features four independently controllable outputs which can output 16amps @230V AC (resistive load). This makes the SyncroSwitch a suitable tool for all your switching needs: High Power, Low Power, Audio or Lighting Signal, Motor Control, Valves or Power of VFD's. Intelligent internal signal routing, Exclusive switching Options, Momentary or Latching output: Many combinations are possible and can be set from the Syncronorm RDM Browser. The DMX address is set remotely (SyncroTools Address Board required) and stored electronically onto non volatile memory and can be adjusted from the Syncronorm RDM Browser.



DIN-Rail Mounting



Relay Contactor



Full RDM Support



Multiple Trigger Levels

TECHNICAL DETAILS

SyncroSwitch

Dimensions	160x90x58 mm DIN RAIL
Weight	0.33 kg
Protection Class	IP 20
Power Supply	24V DC*
Operation Temperature	0.. 40° / 0.. 80% humidity
Certification	CE
Outputs	4x Contact Relay with max. 16A@230VAC (res. load)
Inputs	DMX512 RDM
Order Number	SN-STSW24

*This item is also available with an integrated 230V Power Supply (SN-STSW230).

**This unit requires the SyncroTools DMX address board (SN-STADRB).

